



# STEERINGWAGON

## Professional steeringwagon with pneumatic tires, capacity 500 Kg.

M-STEERINGWAGON-CT is for the professional in particular in the construction industry.

Powdercoated in hammered gray.

Sheetthickness: 3mm.

Platform has rounded corners.

Platform with 4 stanchions holes. (Delivery excl. stanchions)

Puncture proof PU-tyres, red steel rim with double sealed ball bearings.

Pull rod drawbar equipped with natural rubber ergonomic hand-shaped handles.

Stanchions available separately.



15038  
M-STEERINGWAGON-CT

- \* Sheetthickness: 3mm.
- \* Platform has rounded corners.
- \* Pull rod (single turntable control)
- \* Platform with 4 stanchions holes. (Delivery excl. stanchions)
- \* Puncture proof PU-tyres, red steel rim with double sealed ball bearings.



11264  
M-970-Z-RUB



12218  
M-800-CT EINDW.  
PU-tyre (foamed Polyurethane)

Cap. (kg)	Dimensions overall LxWxH (mm)	Dimensions Platform LxW (mm)	Weight (kg)	Wheel Ø(mm)	Wheel	Axle Ø mm	Color	Handgrip LxB (mm)	Article	Article nr.
500	2000x1000x500	2000x1000	77,2	400-8	Puncture proof	25	Hammered-gray	38x20	M-STEERINGWAGON-CT	15038
200			3,5	400-8	Puncture proof	25			M-800-CT EINDW.	12218
									STARLOCK 25MM ((to securing tyre)	10113
	130x55x38		0,12					38x20	m-970-Z RUB	11264
			1,6				Hammered-gray		M-STEERINGWAGON STANCHIONS / 4 pieces L=700mm Ø42,4mm	15037